

All Platform Configurations



Configuration	Foundation 110	Prelude 210	Prelude 212	Prelude 410	Prelude 412	Nemesis 610	Nemesis 612	Nemesis 810	Nemesis 812
Hosting¹	-	2 VM	4 VM	6 VM	8 VM	2 VM	4 VM	6 VM	8 VM
High Availability	-	-	-	-	-	✓	✓	✓	✓
Order Reference	F110	P210	P212	P410	P412	N610	N612	N810	N812
Hardware	Compact industrial chassis	1U Server	1U Server	2U Server	2U Server	4U Cluster	4U Cluster	6U Cluster	6U Cluster
CPU	4-Core	6-Core	8-Core	16-Core	20-Core	6-Core	8-Core	Dual 10-Core	Dual 16-Core
RAM	8 GB	32 GB	32 GB	64 GB	96 GB	32 GB	32 GB	64 GB	128 GB
Storage	512 GB M.2 SATA SSD	2 x 960 GB SSD	2 x 960 GB SSD VM 6 x 1.2 TB HDD Media Faster Controller	2 x 1.92 TB SSD	2 x 1.92 TB SSD VM 6 x 4 TB HDD Media Faster Controller	2 x 1.92 TB SSD	2 x 1.92 TB SSD VM 6 x 8 TB HDD Media	2 x 1.92 TB SSD	2 x 1.92 TB SSD VM 6 x 8 TB HDD Media
Network	2 x 1GB PoE PD Input	6 x 1GB	6 x 1GB 2 x 10 GB	6 x 1GB	6 x 1GB 2 x 10 GB	2 x 1GB	2 x 1GB	6 x 1GB	6 x 1GB 2 x 10 GB
Modules²	2	4	4	6	6	4	4	6	6
Users²	5	5	20	20	50	20	50	50	200

1. These are recommended values only. Results may vary depending on usage environment and hosted systems requirements. 2. Modules and Users license provided with the related model. Additional Modules and/or Users license can be added at time of order, or at any time in the future. The standard warranty for Prelude and Nemesis configurations is 3 years but can be extended to 5 years as part of the optional ISAAC Extended Coverage package. Foundation warranty is 1 year.

Benelux - France Distribution by



□ www.3made.be

✉ info@3made.be