ISAAC®

GEN 5

Prelude 200 Series

Technical Specifications

P220e GEN 4

Hosts	1

System (per host)

CPU Dies	1
CPU Cores / Die	4
CPU Clock (GHz)	3.5
CPU Model	Xeon 6325P
RAM (GB)	32

Network (per host)

1gb Mgmt.	1
10gb Base-T Interconnect	0
25gb SFP Interconnect	0
1gb	2
10gb Base-T	0

Storage (per host)

Usable SSD (GB)	960
Usable HDD (GB)	0

Mechanical (per host)

Rack Unit (RU)	1
Weight (lbs)	25.68
Heat (BTU)	2250
Power (W)	600
AC Auto-ranging (V)	100 ~ 240
Operating Temp (°C)	10 ~ 35

Drawing (per host)

Rail Max Depth: 868 mm
Rail Min Depth: 681 mm



P230

Hosts	1

System (per host)

CPU Dies	1
CPU Cores / Die	8
CPU Clock (GHz)	3.5
CPU Model	Xeon 6507P
RAM (GB)	64

Network (per host)

1gb Mgmt.	1
10gb Base-T Interconnect	0
25gb SFP Interconnect	0
1gb	4
10gb Base-T	4

Storage (per host)

Usable SSD (GB)	960
Usable HDD (GB)	0

Mechanical (per host)

Rack Unit (RU)	1
Weight (lbs)	37.54
Heat (BTU)	3000
Power (W)	800
AC Auto-ranging (V)	100 ~ 240
Operating Temp (°C)	10 ~ 35

Drawing (per host)



P232

Hosts	1

System (per host)

CPU Dies	1
CPU Cores / Die	8
CPU Clock (GHz)	3.5
CPU Model	Xeon 6507P
RAM (GB)	64

Network (per host)

1gb Mgmt.	1
10gb Base-T Interconnect	0
25gb SFP Interconnect	0
1gb	4
10gb Base-T	4

Storage (per host)

Usable SSD (GB)	960
Usable HDD (GB)	7200

Mechanical (per host)

Rack Unit (RU)	1
Weight (lbs)	37.54
Heat (BTU)	3000
Power (W)	800
AC Auto-ranging (V)	100 ~ 240
Operating Temp (°C)	10 ~ 35

Drawing (per host)