

xVision Converter

Dual Fiber to Dual SDI

XVV2FIBER2SDIT1



● Fiber ——— (B) destination point



Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what might soon become your most trustworthy piece of equipment.

Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on professional


A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the xVision Video Converters.

Features

- > **Integrated power supply** with locking PowerCON Connector. Never rely on a cluster of wall-warts again.
- > **Built-in convenience AC** outlet to power nearby projector, TV, laptop, small video projector... Power bar to power both the converter and device not required anymore.
- > **Magnetic stacking system** and non-skid rubber pad for table top application. Saves at least 10 gaffer tape rolls a year.
- > **Multiple mounting options** : C-Clamp, wall-mount adapter, LCD mount adapter and belt adaptor.
- > **Rugged, Tour-ready and aesthetic enclosure** : The sexiest widget in your tool box, that will keep looking good for years to come.
- > **Plug-n-play operation** ; No dials, switches, buttons or menus to fumble with : It just works.
- > Clear and ample status **LED indicators** for quick troubleshooting.
- > **Easy on-the-field identification** with unique color and alphabetic coding system.
- > **SFP-based** video transmission for interoperability with standard SDI over fiber devices.
- > **Relocked and amplified** SDI loop thru
- > **Choice of three** optical connectors, each available as singlemode and multimode types.
- > Proudly designed and assembled **in Canada**.


Ordering Information

XVV2FIBER2SDIT1-1 1 xVision Converter Dual Fiber to Dual SDI



Specifications

Overview



Connections

Video Input Choice of Multimode or Singlemode
Choice of Optical SDI on OpticalCON DUO or OpticalCON QUAD
(see ordering information)

Video Output 4 x 3G/HD/SD SDI BNC

Supported Signals

Video Format Support 3G-SDI Level A and B, HD-SDI, SD-SDI with embedded audio

SMPTE Standards 425 M Level A & B, 424 M, 292 M, 259 M

Physical Specifications

Height 62 mm (2.44 in)

Depth 180 mm (7.08 in)

Width 221 mm (8.7 in)

Weight 2 kg (4.4 lbs)

Environmental Specifications

Operating Humidity 0% to 90% non-condensing

Operating Temperature 0-40 °C

Power requirements

Power Supply Built-in power supply
PowerCON True1 input
PowerCON True1 output (loop-thru)

Power Consumption 45W max.

Voltage Range 100-240V, 50-60Hz

Courtesy Outlet Max 10A, same voltage as input

In the Box

xVision Converter Dual Fiber to Dual SDI AC Mains to PowerCON True1 cable (1.5m, specify plug type at ordering)

Certifications & Compliance

This device complies with the following international standards

